

## Soudaclean 60

Revision: 23/09/2022

Page 1 from 2

### Technical data

Basis	Solvent mixture
Consistency	Fluid
Density	0.70 g/ml
Application temperature	5 °C → 30 °C

\* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. \*\* This information relates to fully cured product.

### Product description

Soudaclean 60 is a fast-drying, non-dissolving cleaning agent. The cleaner is well suited for cleaning and degreasing powder-coated and anodized surfaces (e.g. aluminium window frames) as well as various plastic materials (e.g. PVC window frames) and foil-laminated surfaces (e.g. foil-laminated window frames). Soudaclean 60 removes fresh adhesive residues (after corner angle bonding), adhesive remainders from protection foils, fresh PU-foam, ...

### Properties

- Non-dissolving
- Suitable for powder coated and anodised aluminium (window) profiles
- Suitable for most plastics and metals
- Good compatibility with many types of lacquered surfaces
- Good compatibility with many types of foil-laminated surfaces
- Fast drying
- No streaks
- Leaves no residue

### Applications

- Cleaning of powder-coated and anodized aluminium (window) frames.
- Cleaning of most types of mass-coloured and foil-laminated PVC window frames, sills, cladding, panels and trims.
- Cleaning of lacquered surfaces in the plastics and metal processing industry.
- As post-treatment after using more dissolving cleaners (e.g. Soudaclean 5 or 10).
- Degreasing surfaces in sealant- or bonding applications.

- For removal of fresh adhesive residues after corner angle bonding.
- For removal of dust, adhesive residues of protective film, pencil and pen marks, rubber residues, fresh PU foam and fresh residues of sealant, tar, bitumen.

### Packaging

*Colour:* colourless

*Packaging:* 1L (metal) tin

### Shelf life

At least 24 months in original, unopened packaging at a cool and dry storage place, between +5°C and +25°C.

### Substrates

*Substrates:* white or foil-laminated (veneered) PVC window frames, mass-coloured PVC window frames, extruded aluminium (window) profiles, powder coated aluminium (regular and textured powder coatings), anodised aluminium, ABS, SAN, PC, PMMA, hard PVC

*Nature:* dirty.

*Surface preparation:* No pretreatment required.

### Application method

*Application method:* Bring the product to room temperature prior to application. All surfaces to be treated must be tested for compatibility before use. Soak a clean, lint-free, stain and wrinkle-free cellulose or cotton cloth with Soudaclean 60. Then simply wipe the surface clean (of contaminants). Always work with a clean cloth to avoid contamination of the surface. Make sure there is sufficient ventilation when using the product.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.

---

## Soudaclean 60

---

Revision: 23/09/2022

Page 2 from 2

### Health- and Safety Recommendations

Consult label and material safety data sheet for more information. The user has to check if the product is suitable for the specific application. Take the usual labour hygiene into account. Use only in well-ventilated areas. Always wear gloves and goggles. After contact with skin rinse immediately with soap and water. In case of contact with eyes, wash immediately with plenty of water. If ingested, rinse mouth thoroughly with running water. Avoid swallowing the product. Consult a doctor immediately. Keep out of reach of children. Dangerous. Respect the precautions for use.

### Remarks

- It is recommended to do a compatibility test prior to application.
- Do not store in direct sunlight.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.